Field Machine Tools Pty Ltd
ABN 48 097 691 748
1/26 Shearson Crescent
Mentone VIC 3194
www.fmt.com.au sales@fmt.com.au
Ph: 1300 FMT FMT Fx: 03 9585 7355
International
Ph: 617 3267 6844 Fx: 617 3267 8244

GF Cutters

Specifications

Cutting Range	6mm to 325 mm OD
Wall Thickness	2-10mm
Electric Drive	240v 1.6kW
	Built in speed control
	150 – 270 RPM
Blade Options	Cut only
	Bevel only
	Cut and bevel combo

Description

George Fischer RA Cutter are designed to cut and bevel high-alloy steel (stainless steel), low-alloy and carbon steel, casting materials, non-ferrous metal and plastic pipes in just seconds, using the superior Planetary Cutting Technology**.** This technology provides a square, burr-free and cold machining process using a deformation-free clamping system for tubes and pipes ensuring optimum preparation for the automated welding process. The sturdy design with powerful drive

	RA 2	RA 4	RA 6	RA 8	RA 12
Cutting Range					
Nominal dimension [inch]	1/8” - 2”	¼” – 4”	2” - 6”	4” - 8”	6” - 12”
Pipe O.D., min-max. [mm]	6 - 63	10 - 120	50 - 182	124 - 230	180 - 325
Wall thickness, min-max.[mm]	2 - 5.5	2 - 7	2 - 10	2 - 10	2 - 10
Pipe I.D., min.[mm]	2	6	59	120	173
Weight, approx (Kg)	45	78	95	115	141