

Industrial Vacuums



Heavy-Duty Industrial Vacuum



Heavy-Duty Industrial Vacuum



Air Powered Industrial Vacuum



Soot Vacuum



Specifications	VAC-2-15SS	VAC-3A-15SS	AV-1200-15SS	GTC-540-20SS
Motor(s):	Twin	Triple	•	Twin
Motor Power:	2 ² / ₃ HP (Total)	4 HP (Total)	•	2 ¹ / ₄ HP (Total)
Input Power:	18 Amps, 115 V, 50/60 Hz AC Optional 9 Amps, 230 V, 50/60 Hz AC	13.5 Amps, 230 V, 50/60 Hz AC	•	14 Amps, 115 V, 50/60 Hz AC Optional 7 Amps, 230 V, 50/60 Hz AC
Power Supply Cord:	37', 14-3	37', 14-3	•	37', 14-3
Air Requirements:	•	•	Minimum 50 PSI at 35 CFM	•
Static Water Lift:	83"	83"	170" at 90 PSI	50"
Air Displacement:	198 CFM	270 CFM	125 CFM at 90 PSI	270 CFM
Filtration:	15 Microns Polypropylene/Dacron	15 Microns Polypropylene/Dacron	15 Microns Polypropylene/Dacron	15 Microns Polypropylene/Dacron
Tank:	15 Gallons Stainless Steel	15 Gallons Stainless Steel	15 Gallons Stainless Steel	20 Gallons Stainless Steel
Dry Capacity:	14 Gallons	14 Gallons	14 Gallons	20 Gallons
Wet Capacity:	10 Gallons	10 Gallons	10 Gallons	•
Noise Level:	74 dBA	78 dBA	84 dBA	78 dBA
Special Features:	•	•	Air Powered	Polyethylene Tank Liner Disposable Collection Bag
Dimensions:	15" Diameter Tank x 36" High	15" Diameter Tank x 36" High	15" Diameter Tank x 36" High	15" Diameter Tank x 48" High
Weight:	66 Lbs	70 Lbs	58 Lbs	70 Lbs
Accessories/Prices:	See Page 64	See Page 65	See Page 66	See Page 73



VAC-2-15SS



AV-1200-15SS



GTC-540-20SS

www.goodway.com

STANDARD VACUUMS

Industrial Vacuums



Twin-Motor Large Capacity Vacuum



Triple-Motor Large Capacity Vacuum



Twin-Motor "Walk Behind" Vacuum



Triple-Motor "Walk Behind" Vacuum



Specifications	DV-E2	DV-E3	DV-RV-2	DV-RV-3
Motor(s):	Twin	Triple	Twin	Triple
Motor Power:	2.7 HP (Total)	4.6 HP (Total)	2.7 HP (Total)	4.6 HP (Total)
Input Power:	15 Amps, 115 V, 50/60 Hz AC	13.5 Amps, 230 V, 50/60 Hz AC <i>Optional 27 Amps, 115 V, 50/60 Hz AC</i>	15 amps, 115 V, 50/60 Hz AC	13.5 amps, 230 V, 50/60 Hz AC <i>Optional 27 Amps, 115 V, 50/60 Hz AC</i>
Power Supply Cord:	30', 14-3	30', 14-3	30', 14-3	30', 14-3
Air Requirements:	•	•	•	•
Static Water Lift:	87"	90"	87"	90"
Air Displacement:	224 CFM	353 CFM	224 CFM	353 CFM
Filtration:	3 Microns Polyester Pocket Optional 1 Micron Anti-Static Pocket and 0.3 Microns HEPA	3 Microns Polyester Pocket Optional 1 Micron Anti-Static Pocket and 0.3 Microns HEPA	3 Microns Polyester Pocket Optional 1 Micron Anti-Static Pocket and 0.3 Microns HEPA	3 Microns Polyester Pocket Optional 1 Micron Anti-Static Pocket and 0.3 Microns HEPA
Tank:	27 Gallons Bonderized Steel	27 Gallons Bonderized Steel	14 Gallons Bonderized Steel	14 Gallons Bonderized Steel
Dry Capacity:	27 Gallons	27 Gallons	14 Gallons	14 Gallons
Wet Capacity:	26 Gallons	26 Gallons	•	•
Noise Level:	76 dBA	78 dBA	76 dBA	78 dBA
Special Features:	External Filter Shaker Roll-Out Tank	External Filter Shaker Roll-Out Tank	Front Mounted Floor Tool External Filter Shaker Roll-Out Tank	Front Mounted Floor Tool External Filter Shaker Roll-Out Tank
	•	•	•	•
Dimensions:	20 1/2" Diameter Tank x 60" High	20 1/2" Diameter Tank x 60" High	20 1/2" Diameter Tank x 49" High	20 1/2" Diameter Tank x 49" High
Weight:	175 Lbs	180 Lbs	140 Lbs	145 Lbs
Accessories/Prices:	See Page 67	See Page 67	See Page 68	See Page 68



DV-E2



DV-RV-2

**For Sales Call: +1-203-359-4708
Fax: +1-203-359-9601**

CUSTOM VACUUMS

Two Motor Wet-Dry Vacuum

VAC-2

The VAC-2 Twin-Motor Wet-Dry Vacuum produces a static water lift of 83" and an air displacement of 198 CFM. The unit can be used for liquid recovery or dry debris pickup. It is designed to last, giving years of **dependable performance**. Applications from general cleaning and liquid recovery to picking up metal scrap and chemicals have made the VAC-2 our best seller. The VAC-2 can be used on 15 gallon tanks and 30 or 55 gallon drums.

Features – Benefits

- Two heavy-duty motors – Strong suction**
- Exhaust muffler – Only 78 dBA**
- Three tank sizes – Fits any application**
- Liquid shut-off – Prevents overflow**
- Metal deflector – Will not shatter**
- Reusable filters – Saves money**
- 1½" or 2" hoses – Versatile**

**Three-Year
Limited Warranty**



Specifications

Motor Power:	2½ HP
Input Power:	18 amps, 115 V, 50/60 Hz AC (Optional: 9 amps, 230 V, 50/60 Hz)
Power Supply Cord:	37', 14-3
Static Water Lift:	83"
Air Displacement:	198 CFM
Weight of Vacuum Head:	25 lbs

VAC-2-15SS Industrial Wet-Dry Vacuum including filters and 15 gallon stainless steel tank with handle and casters

VAC-2-30* Industrial Wet-Dry Vacuum including filters and 18"-20" diameter drum adapter ring (no drum)

VAC-2-30-DD Same as VAC-2-30 plus 30 gallon bonderized steel drum, dolly with handle and tool storage box

VAC-2-55* Industrial Wet-Dry Vacuum including filters and 22"-24" diameter drum adapter ring (no drum)

VAC-2-55-DD Same as VAC-2-55 plus 55 gallon bonderized steel drum, dolly with handle and tool storage box

* Note: Fits any standard drum – 30 or 55 gallon depending on model.

Note: Vacuums do not include accessories. Order VAC-KIT-9 or individual accessories shown on pages 81-84.

VAC-KIT-9 1½" Industrial Vacuum Accessory Kit: 10' Neoprene Wire Reinforced Hose, 54" Double Bend Wand, 54" Extension Tube, 5' Extension Tube, 14" Nylon Floor Brush, 14" Squeegee Floor Tool, 14" Rough Surface Fiber Shod Floor Tool, 8" Wall and Overhead Brush, and 27" Steel Crevice Tool

Optional:
Dump Valve (Factory Installed)

DDV-100M 1" Full Flow Ball Valve

DDV-E90 90° Elbow

DDV-675 Garden Hose Connector

VAC-TOOL-TOTE Durabond Tool Storage Pouch

Replacement Filters:

GTC-175 Polypropylene Filter

GTC-176 Dacron Filter

VAC-P-51 Water Guard Filter



Three Motor Wet-Dry Vacuum

VAC-3A

The VAC-3 Triple-Motor Wet-Dry Vacuum produces a static water lift of 83" and an air displacement of 270 CFM. Its **three powerful motors** give it all the power needed for any liquid recovery or dry debris pickup application. The VAC-3A can be used on 15 gallon tanks and 30 or 55 gallon drums.

Features – Benefits

- Three heavy-duty motors – Strong suction**
- Exhaust muffler – Only 78 dBA**
- Three tank sizes – Fits any application**
- Liquid shut-off – Prevents overflow**
- Metal deflector – Will not shatter**
- Reusable filters – Saves money**
- 1½" or 2" hoses – Versatile**



**Three-Year
Limited Warranty**



Specifications

Motor Power:	4 HP
Input Power:	13.5 amps, 230 V, 50/60 Hz AC
Power Supply Cord:	37', 14-3
Static Water Lift:	83"
Air Displacement:	270 CFM
Weight of Vacuum Head:	28 lbs

VAC-3A-15SS Industrial Wet-Dry Vacuum including filters and 15 gallon stainless steel tank with handle and casters

VAC-3A-30* Industrial Wet-Dry Vacuum including filters and 18"-20" diameter drum adapter ring (no drum)

VAC-3A-30-DD Same as VAC-2-30 plus 30 gallon bonderized steel drum, dolly with handle and tool storage box

VAC-3A-55* Industrial Wet-Dry Vacuum including filters and 22"-24" diameter drum adapter ring (no drum)

VAC-3A-55-DD Same as VAC-2-55 plus 55 gallon bonderized steel drum, dolly with handle and tool storage box

* Note: Fits any standard drum – 30 or 55 gallon depending on model.

Note: Vacuums do not include accessories. Order VAC-KIT-9 or individual accessories shown on pages 81-84.

VAC-KIT-9 1½" Industrial Vacuum Accessory Kit: 10' Neoprene Wire Reinforced Hose, 54" Double Bend Wand, 54" Extension Tube, 5' Extension Tube, 14" Nylon Floor Brush, 14" Squeegee Floor Tool, 14" Rough Surface Fiber Shod Floor Tool, 8" Wall and Overhead Brush, and 27" Steel Crevice Tool

Optional:
Dump Valve (Factory Installed)

DDV-100M 1" Full Flow Ball Valve

DDV-E90 90° Elbow

DDV-675 Garden Hose Connector

VAC-TOOL-TOTE Durabond Tool Storage Pouch

Replacement Filters:

GTC-175 Polypropylene Filter

GTC-176 Dacron Filter

VAC-P-51 Water Guard Filter



**For Sales Call: +1-203-359-4708
Fax: +1-203-359-9601**

Air Powered Wet-Dry Vacuum

AV-1200

A proven **workhorse**, the AV-1200 Wet-Dry Vacuum can gulp up to 45 gallons of water per minute. It can produce a static water lift of 170" and an air displacement of 135 CFM. Maintenance departments across all industries count on this vacuum. It recovers everything from machine oil and engine coolant to assorted powders and metal chips quickly and safely. The AV-1200 can be used on 15 gallon tanks and 30 or 55 gallon drums.

Features – Benefits

- Air powered – Shock resistant**
- No moving parts – Maintenance free**
- Three tank sizes – Fits any application**
- Liquid shut-off – Prevents overflow**
- Metal deflector – Will not shatter**
- Reusable filters – Saves money**
- 1½" or 2" hoses – Versatile**

Specifications

- Air Requirements:** Minimum 50 PSI at 35 CFM, Maximum 90 PSI at 50 CFM
- Air Line:** ½" I.D. or larger
- Static Water Lift:** 170" at 90 PSI
- Air Displacement:** 125 CFM at 90 PSI
- Weight of Vacuum Head:** 16 lbs



Power			
The power of the AV-1200 is determined by the air input. Ideal operating pressure for most applications is 50-60 PSI. This will conserve air usage. Operating over 90 PSI wastes air. Use an air regulator if in-plant pressure is too high.			
AIR PRESSURE	WATER LIFT (suction)	AIR DISPLACEMENT (air movement)	AIR CONSUMPTION
50-60 PSI	120"	130 CFM	35 CFM
60-70 PSI	140"	130 CFM	40 CFM
70-80 PSI	160"	130 CFM	45 CFM
80-90 PSI	170"	125 CFM	50 CFM



AV-1200-15SS Air Powered Wet-Dry Vacuum including filters and 15 gallon stainless steel tank with handle and casters

AV-1200-30* Air Powered Wet-Dry Vacuum including filters and 18"-20" diameter drum adapter ring (no drum)

AV-1200-30-DD Same as AV-1200-30 plus 30 gallon bonderized steel drum, dolly with handle and tool storage box

AV-1200-55* Air Powered Wet-Dry Vacuum including filters and 22"-24" diameter drum adapter ring (no drum)

AV-1200-55-DD Same as AV-1200-55 plus 55 gallon bonderized steel drum, dolly with handle and tool storage box

** Note: Fits any standard drum – 30 or 55 gallon depending on model.*

Note: Vacuums do not include accessories. Order VAC-KIT-9-G or individual accessories shown on pages 81-84.

VAC-KIT-9-G 1½" Grounded Industrial Vacuum Accessory Kit: 15' Neoprene Wire Reinforced Hose with Grounding Wire, 54" Double Bend Wand, 54" Extension Tube, 5' Extension Tube, 14" Nylon Floor Brush, 14" Squeegee Floor Tool, 14" Rough Surface Fiber Shod Floor Tool, 8" Wall and Overhead Brush, and 27" Steel Crevice Tool

Optional:

- Dump Valve (Factory Installed)**
- DDV-100M** 1" Full Flow Ball Valve
- DDV-E90** 90° Elbow
- DDV-675** Garden Hose Connector
- VAC-TOOL-TOTE** Durabond Tool Storage Pouch

Replacement Filters:

- GTC-175** Polypropylene Filter
- GTC-176** Dacron Filter
- VAC-P-51** Water Guard Filter

For Sales Call: +1-203-359-4708
Fax: +1-203-359-9601

www.goodway.com

Large Capacity Wet-Dry Vacuums

DV-E2/DV-E3

The DV-E2 Twin-Motor and the DV-E3 Triple-Motor Vacuums combine powerful performance with superior features to tackle a wide range of **extreme applications**. While the DV-E2 produces a static water lift of 87" and an air displacement of 224 CFM, the DV-E3 produces a static water lift of 90" and an air displacement of 353 CFM. Each unit is equipped with a pocket filter which traps particles down to 3 microns and an external filter shaker to keep the filters clear. The collection tank is detachable and can wheel out from under the vacuum without removing the vacuum head or filter.

Features – Benefits

- Two or three heavy-duty motors – Strong suction**
- Detachable roll-out collection tank – Easy dumping**
- External filter shaker – Keeps filter clear**
- Reusable pocket filter – Saves money**
- Filter system traps particles down to 3 microns – Superior filtration**
- Tool basket – Easy storage of accessories**
- 1½", 2" or 3" hoses – Versatile**



Specifications

Motor Power:	
DV-E2:	2.7 HP
DV-E3:	4.6 HP
Input Power:	
DV-E2:	15 amps, 115 V, 50/60 Hz AC, single phase
DV-E3:	13.5 amps, 230 V, 50/60 Hz AC, single phase
	<i>Optional: 27 amps, 115 V, 50/60 Hz, single phase)</i>
Power Supply Cord:	
	30', 14-3
Static Water Lift:	
DV-E2:	87"
DV-E3:	90"
Air Displacement:	
DV-E2:	224 CFM
DV-E3:	353 CFM
Dimensions:	
	20½" diameter tank, 60" high overall
Weight:	175 lbs

DV-E2 Industrial Wet-Dry Vacuum, 115 V, single phase, including filter, external filter shaker, 27 gallon detachable tank with handles, casters and tool basket – **call for customization options and prices**

DV-E3 Industrial Wet-Dry Vacuum, 230 V, single phase, including filter, external filter shaker, 27 gallon detachable tank with handles, casters and tool basket – **call for customization options and prices**

Note: Vacuums do not include accessories. Order DA-KIT-D, DA-KIT-W or individual accessories shown on pages 81-84.

DA-KIT-D 2" Dry DV Vacuum Accessory Kit: 10' Vinyl Crush Proof Hose with Hose Cuff, Hose Adapter for connecting DV Vacuums to 2" hoses, 54" Single Bend Wand, 21" Floor Tool, 18" Bulk Pickup Nozzle, and 24" Steel Crevice Tool

DA-KIT-W 2" Wet DV Vacuum Accessory Kit: 10' Vinyl Crush Proof Hose with Hose Cuff, Hose Adapter for connecting DV Vacuums to 2" hoses, 54" Single Bend Wand, 21" Squeegee Tool, 18" Bulk Pickup Nozzle, and 24" Steel Crevice Tool

Optional:

DA-CAGE Liquid Shut-Off Cage and Float for wet applications

DA-AH-HF HEPA Filter

DA-AH-PF Anti-Static 1 Micron Pocket Filter

Replacement Filter:

DA-PF-14 Polyester 3 Micron Pocket Filter

"Walk Behind" Vacuums

DV-RV-2/DV-RV-3

Equipped with a 28" front mounted floor attachment, the DV-RV-2 and DV-RV-3 Dry Roll-Vac "Walk Behind" Vacuums make cleaning large warehouse and production areas **fast and easy**. While the DV-RV-2 produces a static water lift of 87" and an air displacement of 224 CFM, the DV-RV-3 produces a static water lift of 90" and an air displacement of 353 CFM. Each Roll-Vac is equipped with a pocket filter which traps particles down to 3 microns, an external filter shaker to keep the filters clear, and a detachable collection tank which can wheel out from under the vacuum without removing the vacuum head or filter. The floor attachment can easily be removed to convert the unit into a multi-purpose vacuum with conventional hoses and accessories.

Features – Benefits

28" front mounted floor tool – Fast and easy cleaning of large areas

Two or three heavy-duty motors – Strong suction

Detachable roll-out collection tank – Easy dumping

External filter shaker – Keeps filter clear

Reusable pocket filter – Saves money

Filter system traps particles down to 3 microns – Superior filtration

Tool basket – Easy storage of accessories

1½", 2" or 3" hoses – Versatile



Specifications

Motor Power:

DV-RV-2: 2.7 HP

DV-RV-3: 4.6 HP

Input Power:

DV-RV-2: 15 amps, 115 V, 50/60 Hz AC, single phase

DV-RV-3: 13.5 amps, 230 V, 50/60 Hz AC, single phase

(Optional: 27 amps, 115 V, 50/60 Hz, single phase)

Power Supply Cord:

Static Water Lift: 30', 14-3

DV-RV-2: 87"

DV-RV-3: 90"

Air Displacement:

DV-RV-2: 224 CFM

DV-RV-3: 353 CFM

Dimensions: 20½" diameter tank, 49" high overall

Weight: 140 lbs



DA-AH-HF



DA-AH-PF



DA-PF-14

DV-RV-2 Dry Roll-Vac Vacuum, 115 V, single phase, including 28" front mounted floor attachment, filter, external filter shaker, 14 gallon detachable tank with handle, wheels and casters, and tool basket – **call for customization options and prices**

DV-RV-3 Dry Roll-Vac Vacuum, 230 V, single phase, including 28" front mounted floor attachment, filter, external filter shaker, 14 gallon detachable tank with handle, wheels and casters, and tool basket – **call for customization options and prices**

Note: Vacuums do not include accessories. Order individual accessories shown on pages 81-84.

Optional:

DA-AH-HF HEPA Filter

DA-AH-PF Anti-Static 1 Micron Pocket Filter

Replacement Filter:

DA-PF-14 Polyester 3 Micron Pocket Filter

Replacement Tools:

DA-RV-ATT-1 Bristle for floor attachment

DA-RV-ATT-2 Squeegee Blade for floor attachment